



Wärmeleistungen <sup>1)</sup> Logatrend Therm Direct

Höhe H mm	Breite B mm	Nabenab- stand N mm	Tiefe mm	Expo- nent n	Wärmeleistung bei					Heiz- patrone W	Anstrich- fläche m <sup>2</sup>	Wasser- inhalt l	Gewicht kg
					75/65/ 20°C W <sup>1)</sup>	70/55/ 20°C W <sup>1)</sup>	75/65/ 24°C W <sup>1)</sup>	55/45/ 20°C W <sup>1)</sup>	55/45/ 24°C W <sup>1)</sup>				
740	450	420	30	1,2008	308	254	225	167	141	300	0,5601	2,92	5,1
	500	470	30	1,2007	337	277	246	182	154	300	0,6104	3,12	5,4
	550	520	30	1,2007	366	301	267	198	167	300	0,6606	3,33	5,8
	600	570	30	1,2006	395	325	288	214	180	300	0,7109	3,53	6,2
	750	720	30	1,2005	481	396	352	261	220	500	0,8617	4,14	7,3
	950	920	30	1,2003	597	491	436	323	272	500	1,0628	4,96	8,9
1220	450	420	30	1,2274	503	412	365	269	226	500	0,8681	4,59	7,9
	500	470	30	1,2273	546	448	397	292	245	500	0,9435	4,9	8,4
	550	520	30	1,2272	589	483	428	315	264	500	1,0189	5,2	9
	600	570	30	1,2271	632	518	459	338	284	500	1,0943	5,51	9,6
	750	720	30	1,2268	762	624	553	407	341	750	1,3205	6,42	11,3
1500	450	420	30	1,2309	611	500	443	326	273	600	1,1021	5,79	9,9
	500	470	30	1,2321	671	549	486	358	300	600	1,1994	6,18	10,6
	550	520	30	1,2333	731	598	530	389	326	750	1,2968	6,58	11,4
	600	570	30	1,2345	791	647	573	421	353	750	1,3942	6,97	12,1
	750	720	30	1,2382	972	795	703	516	432	750	1,6864	8,15	14,3
1820	450	420	30	1,214	747	613	544	402	338	750	1,3229	6,96	11,9
	500	470	30	1,2128	815	669	593	439	369	750	1,4391	7,43	12,7
	550	520	30	1,2115	883	725	643	475	400	750	1,5554	7,91	13,6
	600	570	30	1,2102	950	781	693	512	431	1000	1,6716	8,38	14,5
	750	720	30	1,2064	1154	949	842	623	524	1000	2,0203	9,79	17,2
	950	920	30	1,2013	1425	1173	1041	772	650	1000	2,4853	11,67	20,733

<sup>1)</sup> Die angegebene Wärmeleistung entspricht den Wärmeleistungswerten bei Anschluss des Badheizkörpers von unten.  
Wenn Sie die Wärmeleistungswerte bei Anschluss von oben und unten benötigen, sprechen Sie Ihre Buderus Niederlassung an.

