


Declaration of performance

According to Regulation (EU) No. 305/2011
N. EK190

- | | |
|--|---|
| 1. Unique identification code of the product-type | WINDO 120 |
| 2. Intended uses of the product in accordance with the applicable harmonized technical specification | Insert or open fireplace by solid fuel (wood logs) , without hot water production |
| 3. Name or trade mark of the manufacturer (Article 11-5) | EDILKAMIN S.p.A. Via Mascagni, 7 – 20020 Lainate (MI) Italy tel. +39 02 937621 – mail@edilkamin.com |
| 4. Name and address of the agent (Article 12-2) | |
| 5. Assessment and verification system for constancy of performance (Annex 5) | System 3 |
| 6a. Harmonized technical specification Laboratory notified | EN 13229:2001/A1:2003/A2:2004/AC:2006/AC:2007 ACTECO Sri - NB1880 |
| 7. Declared performance | |

| Essential characteristics | Performance | |
|---|--|----------------------------|
| Reaction to fire | A1 | |
| Distance to combustible materials (minimum distance in mm) |  | |
| Risk of burning fuel falling out | Pass | |
| Emission of combustion products | Rated fuel load | Reduced fuel load |
| CO (ref. at 13% O ₂) | 705 mg/Nm ³ - 0,056% | - mg/Nm ³ - - % |
| NO _x (ref. at 13% O ₂) | 134 mg/Nm ³ | - mg/Nm ³ |
| OGC (ref. at 13% O ₂) | 32 mg/Nm ³ | - mg/Nm ³ |
| Particulate matter (ref. at 13% O ₂) | 15 mg/Nm ³ | - mg/Nm ³ |
| Surface temperature | Pass | |
| Electrical safety | NPD | |
| Cleanability | Pass | |
| Maximum operating pressure | - bar | |
| Mechanical resistance (to carry a chimneyflue) | Pass | |
| Thermal output | Rated fuel load | Reduced fuel load |
| Nominal heat output | 19,2 kW | - kW |
| Nominal space heating output | 19,2 kW | - kW |
| Nominal boiler output (to water) | - kW | - kW |
| Energy efficiency | 78,2 % | - % |
| Flue gas temperature | T[261°C] | T[- °C] |

8. Test report number (based on System 3) 1880-CPR-019-20

The performance of the product identified in point 1 is in conformity with the declared performance in points 6a and 7
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Lainate, 30/09/2020

Signed for and on behalf of Edilkamin S.p.A. by:

Legal Representative

Luca Borsatti

